


## DUO: Inserts for Thermo Plastics

### FSUK-DUO



### Dimensions

thread	D	P	L	holesize	wallthickness
M2	3,5	3,1	3,9	3,2	1,3
M2.5	4,4	3,9	5,7	4,0	1,6
M3	4,4	3,9	5,7	4,0	1,6
M3.5	5,2	4,7	7,1	4,8	1,8
M4	6,1	5,5	8,1	5,6	2,1
M5	6,8	6,3	9,5	6,4	2,6
M6	8,5	7,9	12,7	8,0	3,3
M8	10,0	9,5	12,7	9,6	4,5
M10	12,3	11,8	12,7	11,9	6,0

### Advantages

HIGH TORQUE AND PULL OUT  
SUITABLE FOR THIN BOSS WALLS TO MAXIMISE DESIGN SPACE  
DESIGN ALLOWS RAPID INSTALLATION USING HEAT  
AVAILABLE IN SHORTER LENGTHS  
SYMMETRICAL TO AID WITH INSTALLATION

### Description

The Duo range is based on a opposing herringbone knurl with the advantage of it being symmetrical.

Its designed to be installed into drilled or moulded holes using direct heat. (Not Ultrasonic's)

### Comments

DESIGNATION EXAMPLE FSUK DUO B M3 M3 BRASS VERSION  
ONLY AVAILABLE IN BRASS  
MOST SIZES EX STOCK