


DUO: 1

FSUK-DUO



Dimensions

| thread | D | P | L | holesize (+0.1mm-0.0) | wall thickness |
|--------|------|------|------|-----------------------|----------------|
| M2 | 3.5 | 3.1 | 3.9 | 3.2 | 1.3 |
| M2.5 | 4.4 | 3.9 | 5.7 | 4.0 | 1.6 |
| M3 | 4.4 | 3.9 | 5.7 | 4.0 | 1.6 |
| M3.5 | 5.2 | 4.7 | 7.1 | 4.8 | 1.8 |
| M4 | 6.1 | 5.5 | 8.1 | 5.6 | 2.1 |
| M5 | 6.8 | 6.3 | 9.5 | 6.4 | 2.6 |
| M6 | 8.5 | 7.9 | 12.7 | 8.0 | 3.3 |
| M8 | 10.0 | 9.5 | 12.7 | 9.6 | 4.5 |
| M10 | 12.3 | 11.8 | 12.7 | 11.9 | 6.0 |

Description

The Duo range is based on a opposing herringbone knurl with the advantage of it being symmetrical. It's designed to be installed into drilled or moulded holes using direct heat. (Not Ultrasonics)

Advantages

HIGH TORQUE AND PULL OUT SUITABLE FOR THIN BOSS WALLS TO MAXIMISE DESIGN SPACE DESIGN ALLOWS RAPID INSTALLATION USING HEAT AVAILABLE IN SHORTER LENGTHS SYMMETRICAL TO AID WITH INSTALLATION

Comments

EXAMPLE DESIGNATION: FSUK DUO B M3 M3 BRASS
VERSION PLEASE NOTE HOLE SIZES APPLY TO THE POINT REACHED AT THE BOTTOM OF THE INSERT ONLY AVAILABLE IN BRASS MOST SIZES EX STOCK