


ANCHOR:

FSUK-ANCHOR



Dimensions			
thread	E	K	holesize
M2	8.0	2.3	5.9
M2.5	8.0	3.2	5.9
M3	8.0	3.2	5.9
M3.5	9.5	3.8	7.0
M4	9.5	3.8	7.0
M5	11	4.4	8.35
M6	12.5	5.7	9.65
M8	16.0	6.4	13.1
M10	19.0	7.6	15.5
M12	25.4	10.2	19.6
M14	25.4	10.2	19.6
M16	25.4	10.2	19.5

Description

The FSUK Anchor rivet bush is designed with serrations on the spigot and can be used in material as thin as 0.5mm up to 5.9mm.

The spigot is designed to go through the sheet and be riveted over on the back allowing it to go into all types of material. They are generally available in Steel Self colour or Zinc and Clear Pass(C3) and Stainless Steel.

It is designed to be installed into drilled or punched holes.

Please note stock sizes are M3-M10

Advantages

CAN BE INSTALLED MANUALLY OR WITH AN AUTO FEED PRESS
 VERY HIGH PERFORMANCE DUE TO ITS RIVETING ACTION ON
 THE BACK OF THE SHEET METAL
 SUITABLE FOR USE IN DRILLED OR PUNCHED HOLES

Comments

HOW TO SPECIFY:

EXAMPLE FSUK ANCHOR M4 1.6mm S-Z FOR EACH SIZE JUST SPECIFY THE MATERIAL THICKNESS (H)

S= STEEL STST= STAINLESS SC= SELF COLOUR SPECIFY Z FOR ZINC PLATED (TRIVALENT C3) AT THE END OF PART NO

Hole Size tolerance is -0/+0.1mm