



PU: Inserts for Thermo Plastics

FSUK-PUH



FSUK-PU



Dimensions

thread	B	C	D	P	L	H.Size	W.Thickness
M2	0,45	4,8	3,7	3,1	4.0	3,2	1,6
M2.5	0,58	5,5	4,5	3,9	4.8	4,0	2,0
M3	0,58	5,5	4,5	3,9	4.8	4,0	2,0
M3.5	0,74	6,4	5,3	4,7	6.4	4,8	2,4
M4	0,89	7,1	6,1	5,5	7.9	5,6	2,8
M5	1,07	7,9	7,0	6,3	9.5	6,4	3,2
M6	1,32	9,5	8,6	7,9	12.7	8,0	4,0
M8	1,32	11,0	10,2	9,5	12.7	9,6	4,8

Advantages

FAST AND EASY TO INSTALL WITHOUT THE NEED FOR HEAT
HIGH PERFORMANCE
SUITABLE FOR THE MAJORITY OF THERMOPLASTICS
FREE RUNNING THREAD
HEADED VERSION FOR ELECTRICAL CONTACT AND HIGHER PERFORMANCE

Comments

Description

The FSUK PU insert is cold press in insert which is designed with a free running thread and will suit most types of Thermoplastics.

Its designed to be pressed in cold into drilled or moulded holes and due to its combination of fins and knurls can achieve a high performance.